

NO PART OF THIS DOCUMENT MAY BE REPRODUCED WITHOUT PRIOR AGREEMENT AND WRITTEN PERMISSION OF
FORD PERFORMANCE PARTS © Ford Motor Company 2020

PRIOR TO INSTALLATION READ THESE INSTRUCTION COMPETELY
For questions, Call the FORD PERFORMANCE Techline 1-800-367-3788

Please visit <https://www.performanceparts.ford.com> for warranty information



OVERVIEW:

Fits 289/302/351W/351C/351M/400/429/460 engines.

This sheet contains important information regarding the M-6880-B50 Oil Filter Adapter. This adapter allows the oil filter to be rotated to provide greater access and fitment flexibility. This adapter is designed to use a M-6731-FL820 or Motorcraft FL820S.

KIT CONTENTS:

The following parts are included:

- (1) oil filter adapter (blue anodized)
- (1) adapter fastener (black anodized)
- (1) Fel-Pro O-ring FP333053 (small)
- (1) Fel-Pro O-ring FP72494 (large)

FEATURES AND SPECIFICATIONS:

Part Number	M-6880-B50
Material Adapter	6061 Aluminum (blue anodized)
Material Adapter Bolt	7075 or 2024 Aluminum (black anodized)
Adapter Bolt Torque	25 lb * ft

OIL FILTER Part Number

M-6731-FL820 or Motorcraft FL820S:

- Step 1.** Verify that the mating surface on the block is clean and free of imperfections.
- Step 2.** Lightly oil adapter to block O-ring and adapter bolt O-ring.
- Step 3.** Lightly oil internal threads on adapter bolt.
- Step 4.** Loosely install adapter, loosely install oil filter.
- Step 5.** Rotate to best position for your application, torque bolt to 25 LB FT
- Step 6.** Remove filter and lubricate seal. Install filter following manufacturers recommendation for tightening.

Ford Factory Shop Manual purchase options www.motorcraftservice.com